

INDUSTRIAL COMPONENT DATA

SAC-4P- 0,7-PUR/M12FR SORI 1534193 PHOENIX CONTACT

Cable for sensors/actuators SAC-4P 0,7-PUR/M12FR SORI 153..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P- 0,7-PUR/M12FR SORI



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P- 0,7-PUR/M12FR SORI
Catalog number	1534193
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-1A55D5A714
Generated	2026-08-06

Product Overview

Cable for sensors/actuators - SAC-4P - 0,7-PUR/M12FR SORI - 1534193

Sensor/actuator cable, 4-pole, halogen-free, greyish-black RAL 7021, free cable end, to Elbow connection female M12, coding: A, cable length: 0.7 m, Customer variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Cable for sensors/actuators, 4-pole, PUR halogen-free, black-gray RAL 7021, end of free cable, to connection socket angled M12, coded, cable length: 0.7 m, a version of the client

Data commercial

Key order One million five hundred thirty four thousand one hundred ninety three

Packing unit 5 pcs

Key selling BF1CCA -

Minimum order quantity 5 pcs

EAN Four trillion seventeen billion nine hundred eighteen million nine hundred ninety three thousand six hundred thirty four

Unit weight (excluding packaging) 48,460 g

Measures

Cable length 0.7 m

Environmental conditions

Index of protection IP65

IP67

Overview

Current sizing at 40 °C 4 To

Tension sizing 250 V AC

250 V DC

Number of poles Four

Insulation resistance $\geq 10 \text{ M}\Omega$

Encoding A - standard

Status indication Not

Category surge II

Pollution degree Three

Cycles of plug ≥ 100

Tightening torque 0.4 Nm

Material

Class of flammability according to UL 94 HB

Cable

Outer wrap, color black RAL 9005

Outer casing, material PUR

Room temperature (service) -25 °C ... 80 °C (cable, fixed)

-5 °C ... 80 °C (cable, available mobile)

Standards and specifications

Class of flammability according to UL 94 HB

Ratings

eCl@ss

eCl@ss 4.0 Twenty seven million sixty thousand three hundred six

eCl@ss 4.1 Twenty seven million sixty thousand three hundred six

eCl@ss 5.0 Twenty seven million sixty one thousand eight hundred one

eCl@ss 5.1 Twenty seven million sixty one thousand eight hundred

eCl@ss 6.0 Twenty seven million two hundred seventy nine thousand two hundred...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P- 0,7-PUR/M12FR SORI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.