

**INDUSTRIAL COMPONENT DATA**

# SAC-4P-10,0-116/AD 1422687 PHOENIX CONTACT

## Sensor/actuator cable SAC-4P-10,0-116/AD 1422687

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-10,0-116/AD



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | SAC-4P-10,0-116/AD         |
| Catalog number  | 1422687                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 50 Pcs                     |
| Document ID     | EO-16BD54D7C7              |
| Generated       | 2026-08-05                 |

### Product Overview

Sensor/actuator cable - SAC-4P-10,0-116/AD - 1422687

Sensor/Actuator Cable, 4-Pole, Free Cable End, to AD (Pressure Switch) Valve Connectors, Cable Length: 10 m

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

### Additional Product Information

Sensor/actuator cable, 4-position, PUR/PVC, black, free cable end, on Valve connector AD (pressure switch), cable length: 10 m

Key Commercial Data

Orderkey 1422687

Packing unit 1

GTIN 4055626311272

Custom tariff number 85444290

Dimensions

Length of cable 10 m

Ambient conditions

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A

Rated voltage 230 V AC  
230 V DC  
Number of positions 4  
Standards/regulations Valve connector EN 175301-803  
Status display No  
Overvoltage category II  
Degree of pollution 3  
Torque 0.6 Nm  
Material  
Flammability rating according to UL 94 HB  
Valve plug contact material CuSn  
Valve plug contact surface material Sn  
Valve plug contact insert material PA 6.6  
Material housing valve plug TPU  
Sealing material TPU (Seal molded)  
Standards and Regulations  
Standard designation Valve connector  
Standards/regulations EN 175301-803  
Flammability rating according to UL 94 HB  
Classifications  
eCl@ss  
eCl@ss 6.0 27279200  
eCl@ss 7.0 27279218  
eCl@ss 8.0 27279218  
eCl@ss 9.0 27060311  
ETIM  
ETIM 5.0 EC001855  
ETIM 6.0 EC001855  
ETIM 7.0 EC001855  
UNSPSC  
UNSPSC 13.2 31251501

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-10,0-116/AD with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.