

INDUSTRIAL COMPONENT DATA

SAC-4P-10,0-800/M 8FS 1417671 PHOENIX CONTACT

Sensor/actuator cable SAC-4P-10,0-800/M 8FS 1417671

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-10,0-800/M 8FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-10,0-800/M 8FS
Catalog number	1417671
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-187A220C62
Generated	2026-08-04

Product Overview

Sensor/actuator cable - SAC-4P-10,0-800/M 8FS - 1417671

Sensor/actuator cable, 4-position, PUR halogen-free, resistant to welding sparks, highly flexible, gray RAL 7001, free cable end, on Socket straight M8, coding: A, cable length: 10 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 4

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.2 Nm (M8 connectors)
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M8
Number of positions 4
Coding type A
Cable/lineCable length 10 m
Gray, highly flexible PUR [800]
Dimensional drawing
Note Due to the extremely robust outer sheath, this cable should only be stripped in 5 cm increments.
Cable weight 27.1 kg/km
UL AWM Style 20549
Number of positions 4
Shielded no
Cable type Gray, highly flexible PUR [800]
Conductor structure signal line 32x 0.10 mm
AWG signal line 24
Conductor cross section 4x 0.25 mm² (Signal line)
Wire diameter incl. insulation 1.15 mm $\pm 0.05 \text{ mm}$ (Signal line)
External cable diameter 4.50 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PUR
External sheath, color gray RA...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-10,0-800/M 8FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.