

INDUSTRIAL COMPONENT DATA

SAC-4P-10,0-PVC/M12FSD VA 1407976 PHOENIX CONTACT

Sensor/actuator cable SAC-4P-10,0-PVC/M12FSD VA 1407976

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-10,0-PVC/M12FSD VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-10,0-PVC/M12FSD VA
Catalog number	1407976
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-9948B4BDC9
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-4P-10,0-PVC/M12FSD VA - 1407976

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, PVC, black RAL 9005

Key Commercial Data

Orderkey 1407976

Packing unit 1

GTIN 4046356786539

Custom tariff number 85444290

General

Rated voltage 250 V AC

250 V DC

Cable

Cable type PVC black

Cable type (abbreviation) PVC

Cable abbreviation LiYY

UL AWM style 2464 / 1729 (80°C/300 V)

Conductor cross section 4x 0.34 mm² (Signal line)

AWG signal line 22

Conductor structure signal line 19x 0.15 mm

Core diameter including insulation 1.26 mm $\pm$ 0.05 mm

Thickness, insulation $\geq$ 0.23 mm (Core insulation)

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

External sheath, color black RAL 9005

Outer sheath thickness $\geq$ 0.76 mm

External cable diameter D 4.7 mm $\pm$ 0.15 mm

Minimum bending radius, fixed installation 5 x D

Minimum bending radius, flexible installation 10 x D

Cable weight 40 kg/km

Outer sheath, material PVC

Material conductor insulation PVC

Conductor material Bare Cu litz wires

Insulation resistance $\geq$ 200 M Ω *km (at 20 °C)

Conductor resistance $\leq$ 57 Ω /km (at 20 °C)

Nominal voltage, cable $\leq$ 300 V

Test voltage, cable $\geq$ 3000 V

Ambient temperature (operation) -40 °C ... 80 °C (cable, fixed installation)

-25 °C ... 80 °C (cable, flexible installation)

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0 27060306

eCl@ss 4.1 27060306

eCl@ss 5.0 27061801

eCl@ss 5.1 27061801

eCl@ss 6.0 27279200

eCl@ss 7.0 27279218

eCl@ss 8.0 272...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-10,0-PVC/M12FSD VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.