

INDUSTRIAL COMPONENT DATA

SAC-4P-1000,0-PUR/0,34 1403469 PHOENIX CONTACT Cable reel SAC-4P-1000,0-PUR/0,34 1403469

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-1000,0-PUR/0,34



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-1000,0-PUR/0,34
Catalog number	1403469
Category	Data and communication cable
Minimum order	1 Pcs
Document ID	EO-C1D0A79E2D
Generated	2026-08-06

Product Overview

Cable reel - SAC-4P-1000,0-PUR/0,34 - 1403469

By the metre, Cable ring, halogen-free PUR, greyish black RAL 7021, 4-conductors, colour single conductors: brown, white, blue, black

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Cable reel, PUR halogen-free, black-gray RAL 7021

Key Commercial Data

Orderkey 1403469

Packing unit 1

GTIN 4046356654791

Custom tariff number 85444995

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section 4x 0.34 mm²

AWG signal line 22

Conductor structure signal line 42x 0.10 mm
Core diameter including insulation 1.27 mm ± 0.02 mm
Thickness, insulation ≥ 0.21 mm
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.5 mm
External cable diameter D 4.2 mm ± 0.15 mm
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 10 x D
Number of bending cycles 10000000
Minimum bending radius, drag chain applications 10 x D
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 10 m/s²
Cable weight 30 kg/km
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance $\geq 1 \text{ G}\cdot\text{km}$
Conductor resistance $\leq 58 \text{ }\Omega/\text{km}$
Nominal voltage, cable $\leq 300 \text{ V}$
Test voltage, cable $\geq 3000 \text{ V}$
Special properties Flexible cable conduit capable
Silicone-free
Free of substances which would hinder coating with paint or varnish
flexible
Flame resistance in accordance with UL 758/1581 FT2
DIN EN 60332-2-2 (20 s)
Halogen-free in accordance with DIN VDE 0472 part 815
in accordance with DIN EN 50267-2-1
Resistance to oil in accorda...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-1000,0-PUR/0,34 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.