

**INDUSTRIAL COMPONENT DATA**

# SAC-4P-12,0-PUR/M12FST 1419495 PHOENIX CONTACT

## Power cable SAC-4P-12,0-PUR/M12FST 1419495

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-12,0-PUR/M12FST



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | SAC-4P-12,0-PUR/M12FST     |
| Catalog number  | 1419495                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 10 Pcs                     |
| Document ID     | EO-EC5D96D16F              |
| Generated       | 2026-08-06                 |

### Product Overview

Power cable - SAC-4P-12,0-PUR/M12FST - 1419495

Power cable, 4-pole, halogen-free PUR, greyish black RAL 7021, free cable end, to straight female M12, coding: T, cable length: 12 m, for direct current up to 12 A/63 V

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                       |
|--------------|-------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial Field Connectivity (IFC) |
|--------------|-------------------------------------------------------|

### Additional Product Information

Power cable, 4-position, PUR halogen-free, black-gray RAL 7021, free cable end, on Socket straight M12, T-coded, cable length: 12 m

Key Commercial Data

Orderkey 1419495

Packing unit 1

GTIN 4055626170497

Custom tariff number 85444290

Dimensions

Length of cable 12 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP65

IP67

**General**

Rated current at 40°C 12 A

Rated voltage 63 V (DC)

63 V DC

Number of positions 4

Insulation resistance  $\geq 100 \text{ M}\Omega$ 

Coding T power

Standards/regulations M12 connector IEC 61076-2-111

Status display No

Protective circuit/component unwired

Overvoltage category III

Degree of pollution 3

Insertion/withdrawal cycles  $> 100$ **Material**

Flammability rating according to UL 94 V0

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material PA

Material of grip body PA

Material, knurls Zinc die-cast, nickel-plated

**Standards and Regulations**

Standard designation M12 connector

Standards/regulations IEC 61076-2-111

Flammability rating according to UL 94 V0

**Cable**

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9YV1-11Y

UL AWM style 20233 / 10493 (80°C/300 V)

Conductor cross section  $4 \times 1.5 \text{ mm}^2$ 

AWG power supply 16

Conductor structure, voltage supply  $78 \times 0.15 \text{ mm}$ Core diameter including insulation  $2.35 \text{ mm} \pm 0.05 \text{ mm}$ Thickness, insulation  $\geq 0.25 \text{ mm}$ 

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

Length of twist, overall twist 90 mm

External sheath, co...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-12,0-PUR/M12FST with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.