

INDUSTRIAL COMPONENT DATA

SAC-4P-1,5-PUR/8P-M12FS 1347 1426043 PHOENIX CONTACT

Cable for sensors/actuators, 8-pole, PUR halogen-free, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-1,5-PUR/8P-M12FS 1347



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-1,5-PUR/8P-M12FS 1347
Catalog number	1426043
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-E060AE78BC
Generated	2026-08-06

Product Overview

Cable for sensors/actuators, 8-pole, PUR halogen-free, black-gray RAL 7021, end of free cable, Female straight connection M12, coded, cable length: 1.5 m, Variant of the client

Sensor/actuator cable, 8-pole, halogen-free PUR, greyish black RAL 7021, free cable end, to Straight connection female M12, coding: A, cable length: 1.5 m, Customer variant

Sensor/Actuator Cable, 8-Pole, Halogen-Free PUR, Grey-Black RAL 7021, Free Cable End, to Straight Female M12, Coding: A, Cable Length: 1.5 m, Customer Variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Cable for sensors/actuators, 8-pole, PUR halogen-free, black-gray RAL 7021, end of free cable, Female straight connection M12, coded, cable length: 1.5 m, Variant of the client

Data commercial

Key order One million four hundred twenty six thousand forty three

Packing unit 1 pcs

Key selling BF1CFA -

EAN Four trillion fifty five billion six hundred twenty six million four hundred thirty seven thousand three hundred twenty three

Unit weight (excluding packaging) 50,200 g

Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety

Measures

Cable length 1.5 m

Length of peeled end of free cable 50 mm

Environmental conditions

Room temperature (service) -25 °C ... 90 °C (male / female)

Overview

Current sizing at 40 °C 2 To

Tension sizing 30 V AC

30 V DC

Number of poles Eight

Insulation resistance $\geq 100 \text{ M}\Omega$

Encoding A - standard

Status indication Not

Protective circuit/component protection without connect

Category surge II

Pollution degree Three

Cycles of plug ≥ 100 **Material**

Class of flammability according to UL 94 HB

Material contact CuSn

Material contact surface Ni/Au

Material support of contacts TPU GF

Material body grip TPU fire-retardant, self-extinguishing

Material knurled Die-cast zinc, nickel plated

Material of the board NBR

Standards and specifications

Class of flammability according to UL 94 HB

Cable

Type of cable PUR halogen-free black

Cable type (abbreviation) PUR

Abbreviation of cable Li9Y11Y-HF

UL AWM Style 20549 / 10493 (80 °C/300 V)

Sec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-1,5-PUR/8P-M12FS 1347 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.