

INDUSTRIAL COMPONENT DATA

SAC-4P-1,5-PUR/M12FSD 1406440 PHOENIX CONTACT

Sensor/actuator cable SAC-4P-1,5-PUR/M12FSD 1406440

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-1,5-PUR/M12FSD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-1,5-PUR/M12FSD
Catalog number	1406440
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-C1972B105C
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-4P-1,5-PUR/M12FSD - 1406440
Sensor/actuator cable, PUR halogen-free, black-gray RAL 7021

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable
Electrical propertiesNominal voltage UN 48 V AC
60 V DC
Cable/linePUR halogen-free black [PUR]
Dimensional drawing
Cable weight 30 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 4
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm ±0.02 mm

External cable diameter 4.20 mm $\pm$ 0.15 mm
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, white, blue, black
Thickness, insulation $\geq$ 0.21 mm
Thickness, outer sheath approx. 0.50 mm
Overall twist 4 wires, twisted
Max. conductor resistance $\leq$ 58 Ω /km
Insulation resistance $\geq$ 1 G Ω *km
Nominal voltage, cable $\leq$ 300 V
Test voltage $\geq$ 3000 V
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 10 x D
Smallest bending radius, fixed installation 21 mm
Smallest bending radius, movable installation 42 mm
Dynamic load capacity (bending) Max. bending cycles: 10000000, Bending radius: 10 x D, Traversing path: 10 m,
Traversing rate: 3 m/s, Acceleration: 10 m/s²
Halogen-free in accordance with DIN VDE 0472 part 815
in accordance with DIN EN 50267-2-1
Flame resistance in accordance with UL 758/1581 FT2
DIN EN 60332-2-2 (20 s)
Resistance to oil in accordance with DIN EN 6081...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-1,5-PUR/M12FSD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.