

INDUSTRIAL COMPONENT DATA

SAC-4P-15,0-600/M12FS-2L PP VA 1415751 PHOENIX CONTACT Sensor/actuator cable SAC-4P-15,0-600/M12FS-2L PP VA ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-15,0-600/M12FS-2L PP VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-15,0-600/M12FS-2L PP VA
Catalog number	1415751
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-13C1BCD0FF
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-4P-15,0-600/M12FS-2L PP VA - 1415751

Sensor/actuator cable, 4-pole, PP-EPDM, grey RAL 7035, free cable end, to Straight connection female M12, coding: A, with 2 LEDs, cable length: 15 m, with stainless steel knurling

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 4-position, PP-EPDM halogen-free, gray RAL 7035, free cable end, on Socket straight M12, A-coded, with 2 LEDs, cable length: 15 m, with high-grade steel knurl

Key Commercial Data

Orderkey 1415751

Packing unit 1

GTIN 4055626052694

Custom tariff number 85444290

Dimensions

Length of cable 15 m

General

Rated current at 40°C 4 A

Rated voltage 24 V
24 V DC
Number of positions 4
Insulation resistance $\geq 10 \text{ M}\Omega$
Coding A - standard
Status display 2 LEDs
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Material
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material of grip body PP
Material, knurls Stainless steel
Sealing material FKM
Cable
Cable type Halogen-free PP gray
Cable type (abbreviation) 600
Cable abbreviation Li9Y9Y
Conductor cross section $4 \times 0.34 \text{ mm}^2$ (Signal line)
AWG signal line 22
Conductor structure signal line $42 \times 0.10 \text{ mm}$
Core diameter including insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$ (Signal line)
Thickness, insulation $\geq 0.21 \text{ mm}$ (Core insulation)
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
Length of twist, overall twist 48 mm
External sheath, color gray RAL 7035
Outer sheath thickness approx. 0.8 mm
External cable diameter $D 4.7 \text{ mm} \pm 0.15 \text{ mm}$
Minimum bending radius, fixed installation $5 \times D$
Minimum bending radius, flexible installation $10 \times D$
Number of bending cycles 4000000
Minimum bending radius, drag chain applications $10 \times D$
Traversing path 10 m
Traversing rate 3 m/s
A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-15,0-600/M12FS-2L PP VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.