

**INDUSTRIAL COMPONENT DATA**

# MSTB 2,5/ 4-ST-5,08 BK BD:1-4 1710162 PHOENIX CONTACT

## Printed-circuit board connector

Brand: PHOENIX CONTACT | Manufacturer Part Number: MSTB 2,5/ 4-ST-5,08 BK BD:1-4



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | PHOENIX CONTACT               |
| MPN / Reference | MSTB 2,5/ 4-ST-5,08 BK BD:1-4 |
| Catalog number  | 1710162                       |
| Category        | Cable connector               |
| Minimum order   | 50 Pcs                        |
| Document ID     | EO-AC71C88A6A                 |
| Generated       | 2026-08-06                    |

### Product Overview

Printed-circuit board connector

Connector for printed circuit board, nominal section: 2.5 mm², color: black, nominal current: 12 A, nominal voltage (III/2): 320 V, contact surface: Tin, contact type: Female, number of potentials: 4, number of rows: 1, number of poles: 4, number of connections: 4, family of articles: MSTB 2.5/.. -ST, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping form: L Longitudinal slot, conductor connection direction/printed circuit board: 0 °, clamping hook: - Clamping hook, plug-in system: COMBICON MSTB 2.5, locking: without, fixing type: without, packaging type: boxed

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **PHOENIX CONTACT > PCB Connectors (PCC)**

### Additional Product Information

Key Commercial Data

Orderkey 1710162

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4046356074520

Weight per Piece (excluding packing) 6.660 g

Custom tariff number 85366990

Country of origin DE (Germany)

Dimensions

Length [ l ] 18.3 mm

Width [ w ] 20.32 mm

Height [ h ] 15 mm

Pitch 5.08 mm

Dimension a 15.24 mm

General

Range of articles MSTB 2,5/..-ST

Number of positions 4

Connection method Screw connection with tension sleeve

Rated voltage (III/3) 250 V

Connection in acc. with standard EN-VDE

Nominal current IN 12 A

Nominal cross section 2.5 mm<sup>2</sup>

Connection data

Conductor cross section solid min. 0.2 mm<sup>2</sup>

Conductor cross section solid max. 2.5 mm<sup>2</sup>

Conductor cross section flexible min. 0.2 mm<sup>2</sup>

Conductor cross section flexible max. 2.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 2.5 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm<sup>2</sup>

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

2 conductors with same cross section, solid min. 0.2 mm<sup>2</sup>

2 conductors with same cross section, solid max. 1 mm<sup>2</sup>

2 conductors with same cross section, stranded min. 0.2 mm<sup>2</sup>

2 conductors with same cross section, stranded max. 1.5 mm<sup>2</sup>

2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. 0.25 mm<sup>2</sup>

2 conductors with sam...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MSTB 2,5/ 4-ST-5,08 BK BD:1-4 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.