

INDUSTRIAL COMPONENT DATA

SAC-4P-2,0-100/8PFS SH F-MI 1403192 PHOENIX CONTACT

Sensor/actuator cable, 4-pos., PUR/PVC, gray, shielded, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-2,0-100/8PFS SH F-MI



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-2,0-100/8PFS SH F-MI
Catalog number	1403192
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-AAA875CBB3
Generated	2026-08-05

Product Overview

Sensor/actuator cable, 4-pos., PUR/PVC, gray, shielded, free conductor end, on socket, straight M12, 8-pos., A-coded, cable length: 2 m

Sensor/Actuator Cable, 4 poles PUR/PVC, grey, shielded, free cable end, straight connection femaleM12, 8 poles, A-coded, cable length:2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 8

No. of cable outlets 1

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuZn

Contact surface material Ni/Au

Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 2 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M12
Number of positions 8
Coding type A
Cable/linePUR halogen-free gray [280]
Dimensional drawing
Cable weight 36 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 4
Shielded yes
Cable type PUR halogen-free gray [280]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm $\pm 0.02 \text{ mm}$ (Signal line)
External cable diameter 4.95 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PUR
External sheath, color gray RAL 7001
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, white, blue, black
Thickness, insulation $\geq 0.21 \text{ mm}$
Thickness, outer sheath approx. 0.50 mm
Over...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-2,0-100/8PFS SH F-MI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.