

INDUSTRIAL COMPONENT DATA

SAC-4P- 2,0-100/M 8FS BK ONB 1562356 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P- 2,0-100/M 8FS BK ONB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P- 2,0-100/M 8FS BK ONB
Catalog number	1562356
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-9E7BC1D14E
Generated	2026-08-05

Product Overview

Sensor/actuator cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1562356

Packing unit 50 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4046356293457

Weight per Piece (excluding packing) 71.130 g

Custom tariff number 85444290

Country of origin DE (Germany)

Dimensions

Length of cable 2 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR/PVC gray

Cable type (abbreviation) 100

Cable abbreviation LiYY-11Y

Conductor cross section 0.25 mm^2

AWG signal line 24

Conductor structure signal line $32 \times 0.10 \text{ mm}$

Core diameter including insulation $1.32 \text{ mm} \pm 0.02 \text{ mm}$

Thickness, insulation $\geq 0.23 \text{ mm}$ (Core insulation)

$\geq 0.38 \text{ mm}$ (Outer cable sheath)

approx. $3.8 \text{ mm} \pm 0.1 \text{ mm}$ (Inner sheath)

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

External sheath, color gray RAL 7001

External cable diameter $D 4.7 \text{ mm} \pm 0.2 \text{ mm}$

Smallest bending radius, fixed installation 47 mm

Smallest bending radius, m...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P- 2,0-100/M 8FS BK ONB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.