

INDUSTRIAL COMPONENT DATA

SAC-4P- 2,0-600/M12FS FB 1420458 PHOENIX CONTACT

Cable for sensors/actuators SAC-4P- 2,0-600/M12FS FB 1420458

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-2,0-600/M12FS FB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-2,0-600/M12FS FB
Catalog number	1420458
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-E739D0C4FA
Generated	2026-08-05

Product Overview

Cable for sensors/actuators - SAC-4P- 2,0-600/M12FS FB - 1420458

Sensor/actuator cable, 4-pole, PP-EPDM, grey RAL 7035, free cable end and straight connection female M12, cable length: 2 m, Hygienic design, with plastic knurling

Sensor/actuator cable, 4-pin, PP-EPDM, grey RAL 7035, free conductor end, on M12 straight socket, coding: A, cable length: 2 m, Hygienic Design, with plastic ferrule

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Cable for sensors/actuators, 4-pole, PP-EPDM halogen-free, gray RAL 7035, cable length: 2 m, hygienic Design, with knurled plastic

Data commercial

Key order One million four hundred twenty thousand four hundred fifty eight

Packing unit 1 pcs

Key selling BF1CCA -

Minimum order quantity 100 pcs

EAN Four trillion fifty five billion six hundred twenty six million two hundred seventeen thousand seven hundred eighty nine

Unit weight (excluding packaging) 62,000 g

Tariff number tariff Eighty five million four hundred forty four thousand two hundred ninety

Country of origin PL (Poland)

Measures

Cable length 2 m

Environmental conditions

Index of protection IP65

IP67

Overview

Current sizing at 40 °C 4 To

Tension sizing 250 V AC

250 V DC

Number of poles Four

Encoding A - standard

Standards/specifications Plug-in connector M12 to IEC 61076-2-101

Conformity of the material to FDA 21 CFR 177.2600

Status indication Not

Protective circuit/component protection without connect

Category surge II

Pollution degree Three

Tightening torque 0.4 Nm

Material

Material contact CuSn

Material contact surface Ni/Au

Material support of contacts PP

Material body grip PP

Material knurled Polypropylene

Material of the board FKM

Standards and specifications

Name of standard Plug-in connector M12

Standards/specifications IEC 61076-2-101

Name of standard Compliance of the material

Standards/specifications FDA 21 CFR 177.2600

Cable

Type of cable PP halogen-free, grey

Cable type (abbreviation) Six hundred

Abbrevia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-2,0-600/M12FS FB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.