

INDUSTRIAL COMPONENT DATA

SAC-4P-25,0-PUR/M12FR SH VA BK 1066464 PHOENIX CONTACT Sensor/actuator cable SAC-4P-25,0-PUR/M12FR SH VA BK ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-25,0-PUR/M12FR SH VA BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-25,0-PUR/M12FR SH VA BK
Catalog number	1066464
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-FEC8CABCA4
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-4P-25,0-PUR/M12FR SH VA BK - 1066464

Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, shielded, free cable end, to Straight connection female M12, coding: A, cable length: 20 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, shielded, free cable end, on Socket straight M12, A-coded, cable length: 20 m

Key Commercial Data

Orderkey 1066464

Packing unit 1

GTIN 4055626734217

Custom tariff number 85444290

Dimensions

Length of cable 20 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 250 V AC

250 V DC

Number of positions 4

Coding A - standard

Overvoltage category II

Degree of pollution 3

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Stainless steel

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y-V1-C-V1-11Y

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section 4x 0.34 mm² (Signal line)

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.27 mm ±0.02 mm (Signal line)

Thickness, insulation ≥ 0.21 mm

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

Shielding Tinned copper braided shield

Optical shield covering 80 %

External sheath, color black-gray RAL 7021

Outer sheath thickness approx. 0.5 mm

External cable diameter D 4.95 mm ±0.2 mm

Minimum bending...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-25,0-PUR/M12FR SH VA BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.