

INDUSTRIAL COMPONENT DATA

SAC-4P- 2,55-534/AD AE 1102246 PHOENIX CONTACT

Sensor/actuator cable, 4-position, PVC, black, free cable end..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-2,55-534/AD AE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-2,55-534/AD AE
Catalog number	1102246
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-687A678A18
Generated	2026-08-04

Product Overview

Sensor/actuator cable, 4-position, PVC, black, free cable end, on Valve connector AD (pressure switch), cable length: 3 m
 Sensor/Actuator Cable, 4-Pole, Free Cable End, to AD (Pressure Switch) Valve Connectors, Cable Length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1102246

Packing unit 1

GTIN 4055626962177

Custom tariff number 85444290

Drawings

Classifications

Environmental Product Compliance

Drawings

Dimensional drawing

Valve connector, type AD

Schematic diagram

Valve plug connector pin assignment, type AD

Cable cross section

PVC [534]

Back to topEnvironmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Back to topClassifications

eCl@ss

eCl@ss 9.0 27060311

Back to top

ETIM for 1102246 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

Other

Positioning cable feed, field-sided (EF005928)

Other

Type of electrical connection, box-sided (EF005524)

Other

Type of plug-in contact, box-sided (EF008386)

Female (bus)

Cable length (EF000536)

3 m

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Black

With LED indication (EF005950)

No

Screened (EF000881)

No

Cable type (EF000081)

Multi-core

Vulcanize (EF004115)

No

Material contact body (EF008248)

CuSn

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-5 °C

Rated current I_n (EF008250)

4 A

Rated voltage (EF000228)

24 V

Degree of protection (IP) (EF005474)

IP67

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-2,55-534/AD AE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.