

**INDUSTRIAL COMPONENT DATA**

# SAC-4P- 3,0-PUR/M12FSL 1425074 PHOENIX CONTACT Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-3,0-PUR/M12FSL



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | SAC-4P-3,0-PUR/M12FSL      |
| Catalog number  | 1425074                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 1 Pcs                      |
| Document ID     | EO-9E0FABF5C9              |
| Generated       | 2026-08-04                 |

## Product Overview

Power cable

Power cable, 4-pole halogen-free, free cable end, to straight female M12, coding: L, cable length: 3 m, for direct current up to 16 A / 63 V

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                       |
|--------------|-------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial Field Connectivity (IFC) |
|--------------|-------------------------------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 1425074

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 300 (C-2-2017)

GTIN 4055626384122

Weight per Piece (excluding packing) 476.340 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 3 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 16 A

Rated voltage 63 V DC

Number of positions 4

Color handle area black

Insulation resistance  $\geq 100 \text{ M}\Omega$

Coding L - Power

Standards/regulations M12 connector IEC 61076-2-111

Status display No

Protective circuit/component unwired

Overvoltage category III

Degree of pollution 3

Insertion/withdrawal cycles  $\geq 100$

Torque 0.4 Nm (M12 connector)

Material

Flammability rating according to UL 94 V0

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material PA

Material of grip body PA

Material, knurls Zinc die-cast, nickel-plated

Standards and Regulations

Standard designation M12 connector

Standards/regulations IEC 61076-2-111

Flammability rating according to UL 94 V0

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

UL AWM style 20233 / 10493 (80°C/300 V)

Conductor cross section 4x 2.5 mm<sup>2</sup>

AWG power supply 14

Conductor structure, voltage supply 141x 0.15 mm

Core diameter including insulation 2.85 mm  $\pm 0.1 \text{ mm}$

Thickness, insulation  $\geq 0.31 \text{ mm}$

Wire colors brown, white, blue, black

External sheath, color black-gray RAL 7021

Outer s...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-3,0-PUR/M12FSL with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.