

INDUSTRIAL COMPONENT DATA

SAC-4P-30,0-PUR/M12FR-V2A 1512885 PHOENIX CONTACT

Cable for sensors/actuators

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-30,0-PUR/M12FR-V2A



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-30,0-PUR/M12FR-V2A
Catalog number	1512885
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-B36611AA59
Generated	2026-08-05

Product Overview

Cable for sensors/actuators

Sensor/actuator cable, halogen-free PUR, greyish black RAL 7021, cable length: 30 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Cable, sensor/actuator, INTERLOCK-free, halogen-free, black-gray RAL 7021, cable length: 30 m

Business

The code of the application One million five hundred twelve thousand eight hundred eighty five

The amount of the package (C#) 5 Pcs

The minimum quantity of the order 50 Pcs

Note The production is linked to the application (no removal)

GTIN Four trillion seventeen billion nine hundred eighteen million nine hundred ten thousand four hundred thirty three

Weight per piece (excluding packing) 880,000 GRM

The number of corporate and commercial Eighty five million four hundred forty four thousand two hundred ninety

The country-of-origin IN Germany

Measures

The length of the cable (30 m)

The general

Rated voltage 24 V DC

Mating cycles That is > 100

The line

The type of cable PUR halogen-free black

Cable type (code) PURE

The code for the cable Li9Y11Y-HF

The style of the UL AWM 20549 / 10493 (80 °C / 300 V)

The value of the driver 4x 0.34 mm²

The line of the signal WIRE Twenty two

The mounting of the conductive signal line on the 42x 0.10 mm

The diameter of the conductor, including the insulation In (1.27 mm ±0.02 mm)

The density of the wall insulation >= 0.21 mm

The color of the driver brown, black, blue, brown, black

Stranded in total 4 conductors twisted together along

Outer shell, color the black-gray RAL 7021

The thickness of the wall of outer Jacket ca. 0.5 mm

The outer diameter of the cable D More than 4.2 mm (±0.15 mm)

Minimum bend radius of, the position of the fixed 5 x D

Mi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-30,0-PUR/M12FR-V2A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.