

INDUSTRIAL COMPONENT DATA

SAC-4P-35,0-600/M12FR HD 1415666 PHOENIX CONTACT

Cable for sensors/actuators SAC-4P-35,0-600/M12FR HD 1415666

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-35,0-600/M12FR HD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-35,0-600/M12FR HD
Catalog number	1415666
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-77BEA67A92
Generated	2026-08-06

Product Overview

Cable for sensors/actuators - SAC-4P-35,0-600/M12FR HD - 1415666

Cable for sensors/actuators

Sensor/actuator cable, 4-position halogen-free, free cable end, on Socket angled M12, coding: A, cable length: 35 m,
Hygienic design, with high-grade steel knurl

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 4

Application Food processing industry

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsSeal material FKM

Material of grip body PP
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material for screw connection Stainless steel
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Protective circuit unwired
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display No
Status display present No
Connection dataConductor connection
Tightening torque 0.4 Nm
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket angled M12
Number of positions 4
Coding type A
Number of positions 4
Cable/lineCable length 35 m
Dimensional drawing
Cable weight 30 kg/km
Number of positions 4
Shielded no
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm $\pm 0.02 \text{ mm}$ (Signal line)
External cable diameter 4.7 mm $\pm 0.15 \text{ mm}$
Outer sheath, material PP-EPDM
External sheath, color gray RAL 7035
Conductor material Bare Cu litz wires
Material wire insulation PP
Single wire, color brown, white, blue, black
Thickness, insulation $\geq 0.21 \text{ mm}$
Thickness, outer sheath approx. 0.8 mm
Overall....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-35,0-600/M12FR HD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.