

INDUSTRIAL COMPONENT DATA

SAC-4P-5,0-500/M12FR FB 1420972 PHOENIX CONTACT

Sensor/actuator cable SAC-4P-5,0-500/M12FR FB 1420972

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-5,0-500/M12FR FB



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-5,0-500/M12FR FB
Catalog number	1420972
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-BBB20C447C
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-4P-5,0-500/M12FR FB - 1420972

Sensor/Actuator Cable, 4-Pole, Free Cable End, to Elbowed Female M12, Coding: A, Cable Length: 5 m, with Stainless Steel Knurling

Sensor/actuator cable, 4-position, PVC, gray RAL 7001, free cable end, on Socket angled M12, coding: A, cable length: 5 m, with high-grade steel knurl

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Application Food processing industry

Number of positions 4

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsMaterial of grip body PP

Contact material CuSn

Contact surface material Ni/Au
Contact carrier material PP
Material for screw connection Stainless steel
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.4 Nm
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket angled M12
Number of positions 4
Coding type A
Cable/lineCable length 5 m
PVC gray [500]
Dimensional drawing
Cable weight 40 kg/km
UL AWM Style 2464 / 1729 (80°C/300 V)
Number of positions 4
Shielded no
Cable type PVC gray [500]
Conductor structure signal line 19x 0.15 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.26 mm $\pm 0.05 \text{ mm}$
External cable diameter 4.70 mm $\pm 0.15 \text{ mm}$
Outer sheath, material PVC
External sheath, color gray RAL 7001
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color brown, white, blue, black
Thickness, insulation $\geq 0.23 \text{ mm}$ (Core insulation)
Thickness, outer sheath $\geq 0.76 \text{ mm}$
Overall twist 4 wires, twi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-5,0-500/M12FR FB with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.