

INDUSTRIAL COMPONENT DATA

SAC-4P-50,0-PVC/M12FR SH VA 1426105 PHOENIX CONTACT

Cable for sensors/actuators

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-50,0-PVC/M12FR SH VA



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-50,0-PVC/M12FR SH VA
Catalog number	1426105
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-5A545F3B2D
Generated	2026-08-05

Product Overview

Cable for sensors/actuators

Sensor/actuator cable, 4-position, shielded, free cable end, on Socket angled M12, cable length: 50 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 4

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material for screw connection Stainless steel
Electrical propertiesNominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Protective circuit unwired
SignalingStatus display No
Status display present No
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket angled M12
Cable/lineCable length 50 m
PVC black [PVC]
Dimensional drawing
Cable weight 52 kg/km
Number of positions 4
Shielded yes
Cable type PVC black [PVC]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.4 mm ±0.02 mm
External cable diameter 5.9 mm ±0.2 mm
Outer sheath, material PVC
External sheath, color black RAL 9005
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color brown, white, blue, black
Thickness, insulation >= 0.23 mm (Core insulation)
>= 0.76 mm (Outer cable sheath)
Overall twist 4 wires, twisted
Optical shield covering 85 %
Max. conductor resistance max. 58 ?/km (at 20 °C)
Insulation resistance >= 100 M?*km (at 20 °C)
Nominal voltage...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-50,0-PVC/M12FR SH VA with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.