

## INDUSTRIAL COMPONENT DATA

# SAC-4P- 60,0-PUR/M12FS SH 1405012 PHOENIX CONTACT

## Sensor/actuator cable, 4-pole, halogen-free PUR, greyish b..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-60,0-PUR/M12FS SH



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | SAC-4P-60,0-PUR/M12FS SH   |
| Catalog number  | 1405012                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 25 Pcs                     |
| Document ID     | EO-2C09DE7E54              |
| Generated       | 2026-08-03                 |

### Product Overview

Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, shielded, free cable end, in female straight connection M12, coded A, cable length: 60 m

Sensor/actuator cable, 4-pos., PUR, halogen-free, RAL 7021 (black-gray), shielded, free cable end to straight M12 socket, A-coded, cable length: 60 m

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                       |
|--------------|-------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial Field Connectivity (IFC) |
|--------------|-------------------------------------------------------|

### Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 4

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au  
Contact carrier material TPU GF  
Material for screw connection Zinc die-cast, nickel-plated  
Electrical propertiesContact resistance  $\leq 5 \text{ m}\Omega$   
Insulation resistance  $\geq 100 \text{ M}\Omega$   
Nominal voltage UN 48 V AC  
60 V DC  
Nominal current IN 4 A  
Mechanical propertiesMechanical data  
Insertion/withdrawal cycles  $\geq 100$   
SignalingStatus display No  
Status display present No  
ConnectorConnection 1  
Type free cable end  
Connection 2  
Type Socket straight M12  
Number of positions 4  
Coding type A  
Cable/lineCable length 60 m  
PUR halogen-free black [PUR]  
Dimensional drawing  
Cable weight 36 kg/km  
UL AWM Style 20549 / 10493 (80°C/300 V)  
Number of positions 4  
Shielded yes  
Cable type PUR halogen-free black [PUR]  
Conductor structure signal line 42x 0.10 mm  
AWG signal line 22  
Conductor cross section 4x 0.34 mm<sup>2</sup> (Signal line)  
Wire diameter incl. insulation 1.27 mm  $\pm 0.02 \text{ mm}$  (Signal line)  
External cable diameter 4.95 mm  $\pm 0.2 \text{ mm}$   
Outer sheath, material PUR  
External sheath, color black-gray RAL 7021  
Conductor material Bare Cu litz wires  
Material wire insulation PP  
Single wire, color brown, white, blue, black  
Thickness, in...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-60,0-PUR/M12FS SH with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.