

INDUSTRIAL COMPONENT DATA

SAC-4P- 8,0-731/M 8SIFS 1425494 PHOENIX CONTACT

Sensor/actuator cable SAC-4P- 8,0-731/M 8SIFS 1425494

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-8,0-731/M 8SIFS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-8,0-731/M 8SIFS
Catalog number	1425494
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-F5AB5B00A8
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-4P- 8,0-731/M 8SIFS - 1425494

Cable for sensors/actuators

Sensor/actuator cable, 4-position, PVC, black RAL 9005, free cable end, on Socket straight M8 Snap-in, cable length: 8 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 4

No. of cable outlets 1

Shielded no

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Electrical propertiesInsulation resistance >= 100 M?

Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
SignalingStatus display no
Status display present No
ConnectorConnection 1
Type free cable end
Connection 2
Type Socket straight M8 Snap-in
Number of positions 4
Locking type Snap-in
Cable/lineCable length 8 m
PVC black [PVC]
Dimensional drawing
Cable weight 33 kg/km
UL AWM Style 2464 / 1729 (80°C/300 V)
Number of positions 4
Shielded no
Cable type PVC black [PVC]
Conductor structure signal line 14x 0.15 mm
AWG signal line 24
Conductor cross section 4x 0.25 mm² (Signal line)
Wire diameter incl. insulation 1.17 mm ±0.05 mm
External cable diameter 4.40 mm ±0.15 mm
Outer sheath, material PVC
External sheath, color black RAL 9005
Conductor material Bare Cu litz wires
Material wire insulation PVC
Single wire, color brown, white, blue, black
Thickness, insulation ≥ 0.23 mm (Core insulation)
≥ 0.76 mm (Outer cable sheath)
Overall twist 4 wires, twisted
Max. conductor resistance max. 79 ?/km (at 20 °C)
Insulation resistance ≥ 100 M?·km (at 20 °C)
Nominal voltage, cable....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-8,0-731/M 8SIFS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.