

INDUSTRIAL COMPONENT DATA

SAC-4P-M 8MR/0,2-PUR/M 8FR OBS 1105665 PHOENIX CONTACT Sensor/actuator cable, 4-position, PUR halogen-free, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M 8MR/0,2-PUR/M 8FR OBS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M 8MR/0,2-PUR/M 8FR OBS
Catalog number	1105665
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-D677A89937
Generated	2026-08-03

Product Overview

Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, Plug angled M8, on Socket angled M8, cable length: 0.2 m

Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, M8 angled male connector, to M8 angled connection female, cable length: 0.2 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1105665

Packing unit 1

GTIN 4055626989914

Custom tariff number 85444290

Drawings

Ambient conditions

Cable

Classifications

Dimensions

General

Environmental Product Compliance

Drawings

Cable cross section

PUR halogen-free black [PUR]

Back to topDimensions

Length of cable 0.2 m

Back to topAmbient conditions

Degree of protection IP65

IP67

IP68

Back to topGeneral

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 4

Overvoltage category II

Degree of pollution 3

Torque 0.2 Nm

Back to topCable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section 4x 0.25 mm² (Signal line)

AWG signal line 24

Conductor structure signal line 32x 0.10 mm

Core diameter including insulation 1.17 mm ±0.02 mm (Signal line)

Thickness, insulation ≥ 0.21 mm (Core insulation)

approx. 0.5 mm (Outer cable sheath)

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

External sheath, color black-gray RAL 7021

External cable diameter D 3.95 mm ±0.15 mm

Smallest bending radius, fixed installation 20 mm

Smallest bending radius, movable installation 40 mm

Number of bending cycles 10000000

Bending radius 44 mm

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 5 m/s²

Cable weight 23 kg/km

Outer sheath, material PUR

Material conductor insulation PP

Conductor material Bare Cu litz wires

Insulation resistance ≥ 100 G?·km (at 20 °C)

Conductor resis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M 8MR/0,2-PUR/M 8FR OBS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.