

INDUSTRIAL COMPONENT DATA

SAC-4P-M 8MS/0,5-PUR 0,34 1034121 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M 8MS/0,5-PUR 0,34



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M 8MS/0,5-PUR 0,34
Catalog number	1034121
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-1F0A23F3A3
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, M8 straight male connector, to free cable end, cable length: 0.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1034121

Packing unit 1 pc

Minimum order quantity 100 pc

Note Made to Order (non-returnable)

GTIN 4055626540795

Weight per Piece (excluding packing) 21.300 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 0.5 m

General

Number of positions 4

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section 4x 0.34 mm²

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.27 mm ±0.02 mm

Thickness, insulation ≥ 0.21 mm

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

External sheath, color black-gray RAL 7021

Outer sheath thickness approx. 0.5 mm

External cable diameter D 4.2 mm ±0.15 mm

Minimum bending radius, fixed installation 5 x D

Minimum bending radius, flexible installation 10 x D

Number of bending cycles 1000000

Minimum bending radius, drag chain applications 10 x D

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 10 m/s²

Cable weight 30 kg/km

Outer sheath, material PUR

Material conductor insulation PP

Conductor material Bare Cu litz wires

Insulation resistance ≥ 1 G?·km

Conductor resistance ≤ 58 ?/km

Nominal voltage, cable ≤ 300 V

Test voltage, cable ≥ 3000 V

Special properties Flexible cable conduit capable

Silicone-free

Free of substances which would hinder coating with paint or varnish

flexible

Flame resistance in accordance with....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M 8MS/0,5-PUR 0,34 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.