

INDUSTRIAL COMPONENT DATA

SAC-4P-M12FS/15,0-PUR/M12FS 1520097 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12FS/15,0-PUR/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12FS/15,0-PUR/M12FS
Catalog number	1520097
Category	Sensor-actuator patch cord
Minimum order	5 Pcs
Document ID	EO-94CF7FD5C9
Generated	2026-08-06

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, Straight connection female M12, coding: A, a
 Straight connection female M12, coding: A, cable length: 15 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1520097

Packing unit 5 pc

Note Made to Order (non-returnable)

GTIN 4017918942311

Weight per Piece (excluding packing) 459.500 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 15 m

Ambient conditions

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 250 V AC

250 V DC

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Status display No

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Sealing material NBR

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section $4 \times 0.34 \text{ mm}^2$

AWG signal line 22

Conductor structure signal line $42 \times 0.10 \text{ mm}$

Core diameter including insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$

Thickness, insulation $\geq 0.21 \text{ mm}$

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

External sheath, color black-gray RAL 7021

Outer sheath thickness approx. 0.5 mm

External cable diameter $D 4.2 \text{ mm} \pm 0.15 \text{ mm}$

Minimum bending radius, fixed installation $5 \times D$

Minimum bending radius, flexible installati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12FS/15,0-PUR/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.