

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MRT/1,0-PUR/FST SH 1103261 PHOENIX CONTACT Power cable, 4-position, PUR halogen-free, black RAL 90..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MRT/1,0-PUR/FST SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MRT/1,0-PUR/FST SH
Catalog number	1103261
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-54CFF62DEF
Generated	2026-08-05

Product Overview

Power cable, 4-position, PUR halogen-free, black RAL 9005, shielded (Advanced Shielding Technology), Plug angled M12, T-coded, on Socket straight M12, T-coded, cable length: 1 m, For direct current up to 12 A/63 V

Power cable, 4-pole halogen-free, shielded (Advanced Shielding Technology), M12 angled connector, coding: T, to straight female M12, coding: T, cable length: 1 m, for direct current up to 12 A/63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Power cable, 4-position, PUR halogen-free, black RAL 9005, shielded (Advanced Shielding Technology), Plug angled M12, T-coded, on Socket straight M12, T-coded, cable length: 1 m, For direct current up to 12 A/63 V

Key Commercial Data

Orderkey 1103261

Packing unit 1

GTIN 4055626965727

Custom tariff number 85444290

ETIM for 1103261 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Angled

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Female (bus)

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

1 m

Material of cable sheath (EF004136)

Other

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

Yes

Vulcanize (EF004115)

No

Material contact body (EF008248)

Other

Material of contact surface (EF004020)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-30 °C

Rated voltage (EF000228)

63 V

Degree of protection (IP) (EF005474)

IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MRT/1,0-PUR/FST SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.