

**INDUSTRIAL COMPONENT DATA**

# SAC-4P-M12MRT/10,0-PUR WD 1423041 PHOENIX CONTACT

## Power cable SAC-4P-M12MRT/10,0-PUR WD 1423041

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MRT/10,0-PUR WD



|                 |                            |
|-----------------|----------------------------|
| Manufacturer    | PHOENIX CONTACT            |
| MPN / Reference | SAC-4P-M12MRT/10,0-PUR WD  |
| Catalog number  | 1423041                    |
| Category        | Sensor-actuator patch cord |
| Minimum order   | 25 Pcs                     |
| Document ID     | EO-D801180E9C              |
| Generated       | 2026-08-06                 |

### Product Overview

Power cable - SAC-4P-M12MRT/10,0-PUR WD - 1423041

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                       |
|--------------|-------------------------------------------------------|
| Catalog path | PHOENIX CONTACT > Industrial Field Connectivity (IFC) |
|--------------|-------------------------------------------------------|

### Additional Product Information

Power cable, 4-position, PUR halogen-free, black-gray RAL 7021, Plug angled M12, T-coded, on free cable end, cable length: 10 m, Customer version

Key Commercial Data

Orderkey 1423041

Packing unit 1

GTIN 4055626327082

Custom tariff number 85444290

Dimensions

Length of cable 10 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

General

Rated current at 40°C 12 A

Rated voltage 63 V (DC)

63 V DC

Number of positions 4  
Insulation resistance  $\geq 10 \text{ G}\Omega$   
Coding T power  
Status display No  
Protective circuit/component unwired  
Overvoltage category III  
Degree of pollution 3  
Insertion/withdrawal cycles  $> 100$   
Material  
Flammability rating according to UL 94 V0  
Contact material CuZn  
Contact surface material Ni/Au  
Contact carrier material PA  
Material of grip body PA  
Material, knurls Zinc die-cast, nickel-plated  
Standards and Regulations  
Flammability rating according to UL 94 V0  
Cable  
Cable type PUR halogen-free black  
Cable type (abbreviation) PUR  
Cable abbreviation Li9YV1-11Y  
UL AWM style 20233 / 10493 (80°C/300 V)  
Conductor cross section  $4 \times 1.5 \text{ mm}^2$   
AWG power supply 16  
Conductor structure, voltage supply  $78 \times 0.15 \text{ mm}$   
Core diameter including insulation  $2.35 \text{ mm} \pm 0.05 \text{ mm}$   
Thickness, insulation  $\geq 0.25 \text{ mm}$   
Wire colors brown, white, blue, black  
Overall twist 4 wires, twisted  
Length of twist, overall twist 90 mm  
External sheath, color black-gray RAL 7021  
Outer sheath thickness approx. 1.3 mm  
External cable diameter  $D 8.4 \text{ mm} \pm 0.25 \text{ mm}$   
Minimum bending radius, fixed installat...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MRT/10,0-PUR WD with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.