

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/0,3-800/M12FS-3LW 1503687 PHOENIX CONTACT Cable for sensors/actuators, 4-pole, PUR halogen-free..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/0,3-800/M12FS-3LW



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/0,3-800/M12FS-3LW
Catalog number	1503687
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-CA709760C2
Generated	2026-08-05

Product Overview

Cable for sensors/actuators, 4-pole, PUR halogen-free, highly flexible, gray RAL 7001, Plug straight M12, coded A, A connection socket straight M12, a coded, with 3 LEDS, cable length: 0.3 m, LED green, white and yellow
Sensor/actuator cable, 4-position halogen-free, highly flexible, Plug straight M12, coding: A, with 3 LEDS, on Socket straight M12, coding: A, with 3 LEDS, cable length: 0.3 m, With green, white, and yellow LEDS

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 4

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 250 V
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display 3 LEDs
Status display present Yes
Connection dataConductor connection
Tightening torque 0.4 Nm (M12 connector)
ConnectorConnection 1
Type Plug straight M12
Number of positions 4
Coding type A
Number of positions 4
Connection 2
Type Socket straight M12
Number of positions 4
Coding type A
Number of positions 4
Cable/lineCable length 0.3 m
Gray, highly flexible PUR [800]
Dimensional drawing
Note Due to the extremely robust outer sheath, this cable should only be stripped in 5 cm increments.
Cable weight 33.5 kg/km
UL AWM Style 20549
Number of positions 4
Shielded no
Cable type Gray, highly flexible PUR [800]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.3 mm $\pm 0.05 \text{ mm}$ (Signa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/0,3-800/M12FS-3LW with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.