

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 1,0-PUR 0,007 OBS 1097237 PHOENIX CONTACT Sensor/actuator cable, 4-position, PUR halogen-free,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 1,0-PUR 0,07 OBS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 1,0-PUR 0,07 OBS
Catalog number	1097237
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-89D2AA376F
Generated	2026-08-05

Product Overview

Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, A-coded, on free cable end, cable length: 1 m, Customer version

Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, Straight male connector M12, coding: A, to free cable end, cable length: 1 m, Customer variant

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Key Commercial Data

Orderkey 1097237

Packing unit 1

GTIN 4055626938271

Custom tariff number 85444290

Drawings

Ambient conditions

Cable

Dimensions

General

Classifications

Drawings

Cable cross section

PUR halogen-free black [PUR]

Back to topDimensions

Length of cable 1 m

Back to topAmbient conditions

Degree of protection IP65

IP67

Back to topGeneral

Rated current at 40°C 4 A

Rated voltage 250 V AC

250 V DC

Number of positions 4

Overvoltage category II

Degree of pollution 3

Torque 0.4 Nm

Back to topCable

Cable type PUR halogen-free black

Cable type (abbreviation) PUR

Cable abbreviation Li9Y11Y-HF

UL AWM style 20549 / 10493 (80°C/300 V)

Conductor cross section 4x 0.34 mm²

AWG signal line 22

Conductor structure signal line 42x 0.10 mm

Core diameter including insulation 1.27 mm ±0.02 mm

Thickness, insulation ≥ 0.21 mm

Wire colors brown, white, blue, black

Overall twist 4 wires, twisted

External sheath, color black-gray RAL 7021

Outer sheath thickness approx. 0.5 mm

External cable diameter D 4.2 mm ±0.15 mm

Minimum bending radius, fixed installation 5 x D

Minimum bending radius, flexible installation 10 x D

Number of bending cycles 10000000

Minimum bending radius, drag chain applications 10 x D

Traversing path 10 m

Traversing rate 3 m/s

Acceleration 10 m/s²

Cable weight 30 kg/km

Outer sheath, material PUR

Material conductor insulation PP

Conductor material Bare Cu litz wires

Insulation resistance ≥ 1 G?·km

Conductor resistance ≤ 58 ?/km

Nominal voltage, cable ≤ 300 V

Test voltage,....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 1,0-PUR 0,07 OBS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.