

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/10,0-PUR/M8FS 2NC 1413109 PHOENIX

CONTACT Sensor/actuator cable

SAC-4P-M12MS/10,0-PUR/M8FS 2NC ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/10,0-PUR/M8FS 2NC



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/10,0-PUR/M8FS 2NC
Catalog number	1413109
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-B3FF2032E9
Generated	2026-08-05

Product Overview

Sensor/actuator cable - SAC-4P-M12MS/10,0-PUR/M8FS 2NC - 1413109

Sensor/actuator cable, 4 poles, halogen-free PUR, RAL7021 black grey, M12 angled connector, A-coded, in straight M8 female connector, A-coated, cable length: 10m, pin2 not connected

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 4-pos., PUR, halogen-free, black-gray RAL 7021, angled M12 connector, A-coded, to straight M8 socket, A-coded, cable length: 10 m, Pin2 not connected

Key Commercial Data

Orderkey 1413109

Packing unit 1

GTIN 4046356986854

Custom tariff number 85444290

General

Rated voltage 48 V AC

60 V DC

Cable

Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section 3x 0.25 mm²
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm
Thickness, insulation ≥ 0.21 mm (Core insulation)
Wire colors brown, blue, black
Overall twist 3 wires, twisted
Length of twist, overall twist 40 mm
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.5 mm
External cable diameter D 3.6 mm ±0.15 mm
Smallest bending radius, fixed installation 18 mm
Smallest bending radius, movable installation 36 mm
Number of bending cycles 10000000
Bending radius 44 mm
Traversing path 10 m
Traversing rate 3 m/s
Acceleration 10 m/s²
Cable weight 18 kg/km
Outer sheath, material PUR
Material conductor insulation PP
Conductor material Bare Cu litz wires
Insulation resistance ≥ 100 G?·km (at 20 °C)
Conductor resistance ≤ 78 ?/km (at 20 °C)
Nominal voltage, cable ≤ 300 V
Test voltage, cable ≥ 3000 V
Special properties Flexible cable conduit capable
Silicone-free
Free of substances which would hinder coating with paint or varnish
Flame resistance in accor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/10,0-PUR/M8FS 2NC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.