

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/15,0-186 1509474 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/15,0-186



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/15,0-186
Catalog number	1509474
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-E54F2C3876
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole, PUR, grayish-black RAL 7021, Straight male connector M12, coding: A, to free cable end, cable length: 15 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1509474

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 12 (PC-2005)

GTIN 4017918899110

Weight per Piece (excluding packing) 859.400 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 15 m

Stripping length of the free conductor end 50 mm

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65

IP67

IP68

General

Rated current at 40°C 4 A

Rated voltage 250 V AC

250 V DC

Number of positions 4

Insulation resistance $\geq 100 \text{ M}\Omega$

Coding A - standard

Status display No

Protective circuit/component unwired

Overvoltage category II

Degree of pollution 3

Insertion/withdrawal cycles ≥ 100

Torque 0.4 Nm

Material

Flammability rating according to UL 94 HB

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material of grip body TPU, hardly inflammable, self-extinguishing

Material, knurls Zinc die-cast, nickel-plated

Standards and Regulations

Flammability rating according to UL 94 HB

Cable

Cable type PUR POWER 0.75 mm² black

Cable type (abbreviation) 186

Cable abbreviation LiY11Y

UL AWM style 20549 / 1061 (80°C/300 V)

Conductor cross section 4x 0.75 mm² (power line)

AWG signal line 18

Conductor structure signal line 42x 0.15 mm

Core diameter including insulation 1.75 mm $\pm 0.05 \text{ mm}$

Thickness, insulation $\geq 0.23 \text{ mm}$ (Core insulation)

$\geq 0.76 \text{ mm}$ (Outer cable sheath)

Wire colors brown, white, blue, black

Overall twist 4 wires, twi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/15,0-186 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.