

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 5,0-28X 0,12 OD 1564719 PHOENIX CONTACT Sensor/Actuator Cable, 4-Pole, M12 Straight Connector,..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 5,0-28X 0,12 OD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 5,0-28X 0,12 OD
Catalog number	1564719
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-061028A9E6
Generated	2026-08-03

Product Overview

Sensor/Actuator Cable, 4-Pole, M12 Straight Connector, Coding: A, to Free Cable End, Cable Length: 5 m, Outdoor Applications, Knurled Stainless Steel

Cable for sensors/actuators

Sensor/actuator cable, 4-position, Plug straight M12, coding: A, connected with unwired, on free cable end, cable length: 5 m, for outdoor applications, with high-grade steel knurl

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 4

Application External areas

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 V0

Seal material FPM

Material of grip body PP
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material for screw connection Stainless steel
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Protective circuit unwired
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display No
Status display present No
ConnectorConnection 1
Type Plug straight M12
Number of positions 4
Coding type A
Connection 2
Type free cable end
Cable/lineCable length 5 m
PE-X black [28X]
Dimensional drawing
Shielded no
Cable weight 44 kg/km
Cable type PE-X black
Short symbol Li2X2X
Cable type (abbreviation) 28X
External cable diameter 5.2 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PE-X
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Conductor structure signal line 28x 0.15 mm
AWG signal line 20
Conductor cross section 4x 0.5 mm² (Signal line)
Material wire insulation PE-X
Thickness, insulation approx. 0.3 mm (Core insulation)
Wire diameter incl. insulation 1.6 mm $\pm 0.05 \text{ mm}$ (Signal line)
Single wire, color brown, white, blue, black
Overall...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 5,0-28X 0,12 OD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.