

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/5,0-600/M12FS HD 1410443 PHOENIX CONTACT Sensor/actuator cable

SAC-4P-M12MS/5,0-600/M12FS HD 14..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/5,0-600/M12FS HD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/5,0-600/M12FS HD
Catalog number	1410443
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-440C54B26E
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-4P-M12MS/5,0-600/M12FS HD - 1410443

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 4-position, PP-EPDM halogen-free, gray RAL 7035, Plug straight M12, A-coded, on Socket straight M12, A-coded, cable length: 5 m, Hygienic design, with high-grade steel knurl

Key Commercial Data

Orderkey 1410443

Packing unit 1

GTIN 4046356896757

Custom tariff number 85444290

Dimensions

Length of cable 5 m

Ambient conditions

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Number of positions 4
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
Material conformance FDA 21 CFR 177.2600
Status display No
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Torque 0.4 Nm (M12 connector)
Material
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PP
Material of grip body PP
Material, knurls Stainless steel
Sealing material FKM
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Standard designation Material conformance
Standards/regulations FDA 21 CFR 177.2600
Cable
Cable type Halogen-free PP gray
Cable type (abbreviation) 600
Cable abbreviation Li9Y9Y
Conductor cross section $4 \times 0.34 \text{ mm}^2$ (Signal line)
AWG signal line 22
Conductor structure signal line $42 \times 0.10 \text{ mm}$
Core diameter including insulation $1.27 \text{ mm} \pm 0.02 \text{ mm}$ (Signal line)
Thickness, insulation $\geq 0.21 \text{ mm}$ (Core insulation)
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
Length of twist,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/5,0-600/M12FS HD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.