

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 5,0-BF145 1409762 PHOENIX CONTACT

Sensor/actuator cable SAC-4P-M12MS/ 5,0-BF145 1409762

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 5,0-BF145



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 5,0-BF145
Catalog number	1409762
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-18A2906412
Generated	2026-08-03

Product Overview

Sensor/actuator cable - SAC-4P-M12MS/ 5,0-BF145 - 1409762

Sensor/actuator cable, halogen-free POC, irradiation cross-linked, black RAL 9005, M12 straight male connector, coding: A-encoded, free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, POC halogen-free, irradiated, black RAL 9005, Plug straight M12, A-coded, on free cable end, cable length: 5 m

Key Commercial Data

Orderkey 1409762

Packing unit 1

GTIN 4046356881296

Custom tariff number 85444290

Dimensions

Length of cable 5 m

Ambient conditions

Degree of protection IP65

IP67

General

Rated current at 40°C 4 A
Rated voltage 250 V AC
250 V DC
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Torque 0.4 Nm
Cable
Cable type POC irradiated halogen-free black
Cable type (abbreviation) BF 145
Conductor cross section $4 \times 0.75 \text{ mm}^2$
AWG signal line 18
Core diameter including insulation 2.2 mm
Wire colors black 1, black 2, black 3, black 4
Overall twist 4 wires around filler to the core
External sheath, color black RAL 9005
External cable diameter D 6.9 mm
Minimum bending radius, fixed installation $4 \times D$
Minimum bending radius, flexible installation $8 \times D$
Cable weight 75 kg/km
Outer sheath, material POC
Material conductor insulation POC
Conductor material Tin-plated Cu litz wires
Nominal voltage, cable 300 V
Test voltage, cable 3500 V
Special properties Irradiated
Flame resistance according to IEC 60332-1
according to EN 50265-2-1
Halogen-free according to IEC 60754-1
According to EN 50267-2-1
Concentration of fumes in accordance with IEC 61034
EN 50268-2
Ambient temperature (operation) $-55^\circ\text{C} \dots 145^\circ\text{C}$ (cable, fixed installation)
 $-35^\circ\text{C} \dots 120^\circ\text{C}$ (cable, flexible installation)
Classifications
eCI@ss
eCI@ss 4.0 270603...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 5,0-BF145 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.