

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 5,0-PUR/M12FS 1694075 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 5,0-PUR/M12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 5,0-PUR/M12FS
Catalog number	1694075
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-209D7A774B
Generated	2026-08-05

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole halogen-free, M12 straight connector, encoding: A, to M12 straight female, coding: A, cable length: 5 m

Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, coding: A, on Socket straight M12, coding: A, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Number of positions 4

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.4 Nm
ConnectorConnection 1
Type Plug straight M12
Number of positions 4
Coding type A
Connection 2
Type Socket straight M12
Number of positions 4
Coding type A
Cable/lineCable length 5 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 30 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 4
Shielded no
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm $\pm 0.02 \text{ mm}$
External cable diameter 4.20 mm $\pm 0.15 \text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material Bare Cu litz wires
Material wire insulation P...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 5,0-PUR/M12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.