

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MSL/10,0-PUR/FSL 1261819 PHOENIX CONTACT

Power cable, 4-pole, halogen-free PUR, greyish black RAL ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MSL/10,0-PUR/FSL



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MSL/10,0-PUR/FSL
Catalog number	1261819
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-45D219D769
Generated	2026-08-06

Product Overview

Power cable, 4-pole, halogen-free PUR, greyish black RAL 7021, Straight connector M12, coding: L, to Straight female M12, coding: L, cable length: 10 m, for direct current up to 16 A / 63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1261819 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Female (bus)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
10 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
Yes
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
No
Vulcanize (EF004115)
No
Material contact body (EF008248)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-50 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-30 °C
Rated voltage (EF000228)
63 V
Degree of protection (IP) (EF005474)
IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MSL/10,0-PUR/FSL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.