

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MST/10,0-PUR WD 1423036 PHOENIX CONTACT

Power cable SAC-4P-M12MST/10,0-PUR WD 1423036

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MST/10,0-PUR WD



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MST/10,0-PUR WD
Catalog number	1423036
Category	Sensor-actuator patch cord
Minimum order	25 Pcs
Document ID	EO-3E2DAF77DB
Generated	2026-08-06

Product Overview

Power cable - SAC-4P-M12MST/10,0-PUR WD - 1423036

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Power cable, 4-position, PUR halogen-free, black-gray RAL 7021, Plug straight M12, T-coded, on free cable end, cable length: 10 m, Customer version

Key Commercial Data

Orderkey 1423036

Packing unit 1

GTIN 4055626327044

Custom tariff number 85444290

Dimensions

Length of cable 10 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 85 °C (Plug / socket)

General

Rated current at 40°C 12 A

Rated voltage 63 V (DC)

63 V DC

Number of positions 4
Insulation resistance $\geq 10 \text{ G}\Omega$
Coding T power
Status display No
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Insertion/withdrawal cycles > 100
Material
Flammability rating according to UL 94 V0
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material PA
Material of grip body PA
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9YV1-11Y
UL AWM style 20233 / 10493 (80°C/300 V)
Conductor cross section $4 \times 1.5 \text{ mm}^2$
AWG power supply 16
Conductor structure, voltage supply $78 \times 0.15 \text{ mm}$
Core diameter including insulation $2.35 \text{ mm} \pm 0.05 \text{ mm}$
Thickness, insulation $\geq 0.25 \text{ mm}$
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
Length of twist, overall twist 90 mm
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 1.3 mm
External cable diameter $D 8.4 \text{ mm} \pm 0.25 \text{ mm}$
Minimum bending radius, fixed install...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MST/10,0-PUR WD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.