

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MST/ 5,0-110/M12FST 1089998 PHOENIX CONTACT Power cable, 4-pole, PVC, grayish black RAL 7021, Stra..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MST/ 5,0-110/M12FST



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MST/ 5,0-110/M12FST
Catalog number	1089998
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-5451721C10
Generated	2026-08-05

Product Overview

Power cable, 4-pole, PVC, grayish black RAL 7021, Straight connector M12, coding: T, to Straight female M12, coding: T, cable length: 5 m, for direct current up to 12 A/63 V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1089998 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Straight

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)

Female (bus)

Positioning cable feed, box-sided (EF005927)

Straight

Cable length (EF000536)

5 m

Material of cable sheath (EF004136)

Polyvinyl chloride (PVC)

Halogen free (EF000025)

Yes

Colour cable sheath (EF008249)

Other

With LED indication (EF005950)

No

Screened (EF000881)

No

Vulcanize (EF004115)

No

Material contact body (EF008248)

Other

Material of contact surface (EF004020)

Other

Permitted cable outer temperature after assembling without vibration (EF001686)

-40 °C

Permitted cable outer temperature during assembling/handling (EF001685)

-20 °C

Rated voltage (EF000228)

63 V

Degree of protection (IP) (EF005474)

IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MST/ 5,0-110/M12FST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.