


INDUSTRIAL COMPONENT DATA

SAC-4P-M12Y/2X1,0-PUR/C-1L-V 1500479 PHOENIX CONTACT

Sensor/actuator cable, 3-pole, halogen-free PUR, black ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12Y/2X1,0-PUR/C-1L-V



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12Y/2X1,0-PUR/C-1L-V
Catalog number	1500479
Category	Sensor-actuator patch cord
Minimum order	100 Pcs
Document ID	EO-AE0504BC96
Generated	2026-08-04

Product Overview

Sensor/actuator cable, 3-pole, halogen-free PUR, black RAL 9005, M12 straight connector, coding: A, a Valve connector C (8 mm) and Valve connector C (8 mm), cable length: 1 m

Sensor/Actuator Cable, Halogen-Free 3-Pole, M12 Straight Connector, Coding: A, A C Valve Connectors (8mm) and C Valve Connectors (8mm), Cable Length: 1 m

Sensor/actuator cable, 3-position halogen-free, Plug straight M12, coding: A, on Valve connector C (8 mm) and Valve connector C (8 mm), cable length: 1 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Distributor with cable

Number of positions 3

No. of cable outlets 2

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Material housing valve plug PBT

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Contact material CuSn
Valve plug contact insert material PBT
Contact surface material Ag
Material for screw connection Zinc die-cast, nickel-plated
Electrical propertiesContact resistance $\leq 5 \text{ m}\Omega$
Insulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
ConnectorConnection 1
Type Plug straight M12
Coding type A
Connection 2
Type Valve connector C (8 mm)
Material CuSn (Contact)
Ag (Contact surface)
PBT (Contact carriers)
PBT (Housing)
Connection 3
Type Valve connector C (8 mm)
Material CuSn (Contact)
Ag (Contact surface)
PBT (Contact carriers)
PBT (Housing)
Cable/lineCable length 1 m
PUR halogen-free black [PUO]
Dimensional drawing
Shielded no
Cable type PUR halogen-free black
Short symbol Li9Y11Y
Cable type (abbreviation) PUO
External cable diameter 5.9 mm $\pm 0.1 \text{ mm}$
Outer sheath, material PUR
External sheath, color black RAL 9005
Conductor material Tin-plated Cu litz wires
Conductor structure signal line 16x 0.20 mm
AWG signal line 20
Conducto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12Y/2X1,0-PUR/C-1L-V with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.