

**INDUSTRIAL COMPONENT DATA**

# UCS SW 125-F 9005 2203365 PHOENIX CONTACT Side panel

Brand: PHOENIX CONTACT | Manufacturer Part Number: UCS SW 125-F 9005



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | PHOENIX CONTACT                  |
| MPN / Reference | UCS SW 125-F 9005                |
| Catalog number  | 2203365                          |
| Category        | Extruded profile modular housing |
| Minimum order   | 10 Pcs                           |
| Document ID     | EO-F1B69A2675                    |
| Generated       | 2026-08-06                       |

## Product Overview

Side panel

Sidewall for use with housing halves in sizes 125 x 87 mm and 145 x 125 mm; wall thickness 2 mm; total housing height 47 mm; polycarbonate material; black color similar to RAL 9005

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                |
|--------------|--------------------------------|
| Catalog path | PHOENIX CONTACT > Housing (HS) |
|--------------|--------------------------------|

## Additional Product Information

Key Commercial Data

Orderkey 2203365

Packing unit 20 pc

GTIN 4055626427775

Weight per Piece (excluding packing) 9.110 g

Custom tariff number 85389099

Country of origin DE (Germany)

Item properties

Type UCS SW 125-F 9005

Order No. 2203365

Housing type Universal housings

Type flat

Measurements

Width [ w ] 96 mm

Height [ h ] 39.5 mm  
Depth [ d ] 2 mm  
Material specifications  
Color (RAL) black (9005)  
Insulating material PC  
CTI according to IEC 60112 2  
Flammability rating according to UL 94 V0  
Housing material PC  
Ambient conditions  
Ambient temperature (storage/transport) -40 °C ... 70 °C  
Ambient temperature (assembly) -5 °C ... 100 °C  
Ambient temperature (operation) -40 °C ... 100 °C (depending on power dissipation)  
Mechanical strength/tumbling barrel  
Specification IEC 60068-2-31:2008-05  
Height of fall 50 cm  
Number of drop cycles 50  
Thermostability (ball thrust test)  
Specification IEC 60695-10-2:2014-02  
Temperature 125 °C  
Test duration 1 h  
Force 20 N  
Test for assessing the risk of fire (glow wire)  
Specification DIN EN 60695-2-11 (VDE 0471-2-11):2014-11  
Temperature 850 °C  
Time of exposure 30 s  
Test for substances that would hinder coating with paint or varnish  
Result Test passed  
Specification VW PV 3.10.7:2005-02  
Packaging information  
Pieces per package 20  
Denomination packing units Pcs.  
Standards and regulations  
Flammability rating according to UL 94 V0  
Classifications  
eCl@ss 5.127180506eCl@ss 6.027180800eCl@ss 7.027182702eCl@ss 8.027182702eCl@ss 9.027182702  
ETIM 5.0EC001031ETIM 6....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UCS SW 125-F 9005 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.