

INDUSTRIAL COMPONENT DATA

SAC-4P-M8MS/1,8-350/M8FS 0,34 1422552 PHOENIX CONTACT Sensor/actuator cable SAC-4P-M8MS/1,8-350/M8FS 0,34 14..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M8MS/1,8-350/M8FS 0,34



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M8MS/1,8-350/M8FS 0,34
Catalog number	1422552
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-49FE451422
Generated	2026-08-06

Product Overview

Sensor/actuator cable - SAC-4P-M8MS/1,8-350/M8FS 0,34 - 1422552

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, cable length: 1.8 m

Key Commercial Data

Orderkey 1422552

Packing unit 1

GTIN 4055626306964

Custom tariff number 85444290

Dimensions

Length of cable 1.8 m

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 4

Coding A - standard
Standards/regulations M8 connector IEC 61076-2-104
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9Y11Y-HF
UL AWM style 20549
Conductor cross section 4x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm (Signal line)
Thickness, insulation ≥ 0.21 mm (Core insulation)
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 0.7 mm
External cable diameter D 4.4 mm ±0.15 mm
Smallest bending radius, fixed installation 22 mm
Smallest bendi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M8MS/1,8-350/M8FS 0,34 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.