

INDUSTRIAL COMPONENT DATA

SAC-4P-M8MS/2-PUR/M12FSSH OBS 1423326 PHOENIX CONTACT Sensor/actuator cable

SAC-4P-M8MS/2-PUR/M12FSSH OBS 14..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M8MS/2-PUR/M12FSSH OBS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M8MS/2-PUR/M12FSSH OBS
Catalog number	1423326
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-86C33A8466
Generated	2026-08-03

Product Overview

Sensor/actuator cable - SAC-4P-M8MS/2-PUR/M12FSSH OBS - 1423326

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **PHOENIX CONTACT > Industrial Field Connectivity (IFC)**

Additional Product Information

Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, shielded, cable length: 2 m

Key Commercial Data

Orderkey 1423326

Packing unit 1

GTIN 4055626339214

Custom tariff number 85444290

Dimensions

Length of cable 2 m

General

Rated current at 40°C 4 A

Rated voltage 48 V AC

60 V DC

Number of positions 4

Coding A - standard
Status display No
Overvoltage category II
Degree of pollution 3
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Flammability rating according to UL 94 HB
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation LiF9YC11Y
UL AWM style 20549
Conductor cross section 4x 0.25 mm² (Signal line)
AWG signal line 24
Conductor structure signal line 32x 0.10 mm
Core diameter including insulation 1.17 mm ±0.02 mm (Signal line)
Thickness, insulation ≥ 0.21 mm (Core insulation)
approx. 0.5 mm (Outer cable sheath)
Wire colors brown, white, blue, black
Overall twist 4 wires, twisted
Shielding Braided copper wires
Optical shield covering 80 %
External sheath, color black-gray RAL 7021
External cable diameter D 4.7 mm ±0.15 mm
Smallest bending radius, fixed installation 24 mm
Smallest bending radius, movable installation 48 mm
Number of bending cycles 1000000
Bending radius 48 mm
Trav...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M8MS/2-PUR/M12FSSH OBS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.