

INDUSTRIAL COMPONENT DATA

MKKDSNH 1,5/ 2-5,08 BD:21,22 1710151 PHOENIX CONTACT PCB terminal block base

Brand: PHOENIX CONTACT | Manufacturer Part Number: MKKDSNH 1,5/ 2-5,08 BD:21,22



Manufacturer	PHOENIX CONTACT
MPN / Reference	MKKDSNH 1,5/ 2-5,08 BD:21,22
Catalog number	1710151
Category	Printed circuit board terminal
Minimum order	50 Pcs
Document ID	EO-11FC73B48F
Generated	2026-08-05

Product Overview

PCB terminal block base

Terminal block for printed circuit board, nominal current: 13.5 A, nominal voltage (III/2): 400 V, nominal cross-section: 1.5 mm², number of potentials: 2, number of rows: 1, number of poles per row: 2, article family: MKKDSNH 1.5, pitch: 5.08 mm, connection type: Screw connection with traction capsule, screw clamping method: L Longitudinal slot, mounting: Wave soldering, conductor/printed circuit board connection direction: 0 °, color: green, Pin arrangement: Linear pin arrangement, Pin length [P]: 3.5 mm, number of solder pins per potential: 1, packaging type: boxed. The item can be aligned with different numbers of poles!

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 1710151

Packing unit 1

GTIN 4055626134161

Custom tariff number 85369010

Dimensions

Length [L] 8.6 mm

Pitch 5.08 mm

Dimension a 5.08 mm

Width [w] 10.16 mm

Height 19.1 mm

Height [h] 22.6 mm

Solder pin [P] 3.5 mm

Hole diameter 1.3 mm

General

Range of articles MKKDSNH 1,5

Insulating material group I

Rated voltage (III/2) 400 V

Nominal current IN 13.5 A

Nominal cross section 1.5 mm²

Solder pin surface

Flammability rating according to UL 94 V0

Number of positions 2

Standards and Regulations

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127261100eCl@ss 6.027261100eCl@ss 7.027440401eCl@ss 8.027440401eCl@ss 9.027440401

ETIM 5.0EC002643ETIM 6.0EC002643

UNSPSC 13.239121432

ETIM for 1710151 Connectors (EC002643)

Feature Name

Feature Value

Height (EF000040)

22.6 mm

Number of electrical connections (EF008252)

2

Number of levels (EF002659)

1

Modular spacing connections (EF006827)

5.08 mm

Rated current In (EF008250)

13.5 A

Rated voltage (EF000228)

400 V

Rated surge voltage (EF002993)

4 kV

Over voltage category (EF006785)

III

Pollution degree (EF006786)

2

Connection type conductor (EF006821)

Screw connection

Connectable conductor cross section solid-core (EF007337)

0.14 mm²

Connectable conductor cross section fine-strand with cab...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MKKDSNH 1,5/ 2-5,08 BD:21,22 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.