

INDUSTRIAL COMPONENT DATA

SAC-4P-MR/ 3,0-547/FR SCO BK 1424972 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-MR/ 3,0-547/FR SCO BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-MR/ 3,0-547/FR SCO BK
Catalog number	1424972
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-1D3C0840F1
Generated	2026-08-03

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 4-pole, PVC, yellow, Angled male connector M12, coding: A, to Elbowed connection female M12, coding: A, cable length: 3 m

Sensor/actuator cable, 4-position, PVC, yellow, Plug angled M12, coding: A, on Socket angled M12, coding: A, cable length: 3 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Application Standard, U.S. cables

Number of positions 4

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Seal material NBR

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au

Contact carrier material TPU GF

Material for screw connection Zinc die-cast, nickel-plated

Outer sheath, material PVC

Electrical properties Insulation resistance $\geq 10 \text{ M}\Omega$

Nominal voltage UN 250 V AC

250 V DC

Nominal current IN 4 A

Signaling Status display no

Status display present No

Connection data Conductor connection

Tightening torque 0.4 Nm (M12 connector)

Connector Connection 1

Type Plug angled M12

Number of positions 4

Coding type A

Connection 2

Type Socket angled M12

Number of positions 4

Coding type A

Cable/line Cable length 3 m

PVC AWG 18 yellow 105°C [547]

Dimensional drawing

UL AWM Style 2517 (105 °C / 300 V)

Number of positions 4

Shielded no

Cable type PVC AWG 18 yellow 105°C [547]

Conductor structure signal line 41x 0.16 mm

AWG signal line 18

Wire diameter incl. insulation 1.7 mm $\pm 0.03 \text{ mm}$

External cable diameter 6.00 mm $\pm 0.2 \text{ mm}$

Outer sheath, material PVC

External sheath, color yellow

Conductor material Tin-plated Cu litz wires

Material wire insulation PVC

Single wire, color brown, white, blue, black

Overall twist 4 wires, twisted

Nomi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-MR/ 3,0-547/FR SCO BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.