

INDUSTRIAL COMPONENT DATA

SAC-4P-MRDC2/ 5,0-936 SCO 1410296 PHOENIX CONTACT

Bus system cable, PROFINET, 4-pos., RADOX

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-MRDC2/ 5,0-936 SCO



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-MRDC2/ 5,0-936 SCO
Catalog number	1410296
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-9725F3A8AB
Generated	2026-08-04

Product Overview

Bus system cable, PROFINET, 4-pos., RADOX

Cable for bus system, PROFINET, 4 poles, RADOX® GKW S, black RAL 9005, angled male connector M12 SPEEDCON, codif. D, to free cable end, cable length: 5 m, 270° coding

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1410296

Packing unit 1 pc

Minimum order quantity 50 pc

GTIN 4046356895095

Weight per Piece (excluding packing) 0.000 g

Custom tariff number 85444290

Country of origin PL (Poland)

Drawings

General

Standards and Regulations

Environmental Product Compliance

Dimensions

[Material](#)

[Cable](#)

[Classifications](#)

[Drawings](#)

[Cable cross section](#)

[PROFINET railway applications \[936\]](#)

[Back to top](#)[Dimensions](#)

[Length of cable 5 m](#)

[Stripping length of the free conductor end 50 mm](#)

[Back to top](#)[General](#)

[Rated current at 40°C 4 A](#)

[Rated voltage 48 V AC](#)

[60 V DC](#)

[Number of positions 4](#)

[Coding D - data](#)

[Signal type/category PROFINET](#)

[Overvoltage category II](#)

[Degree of pollution 3](#)

[Back to top](#)[Material](#)

[Flammability rating according to UL 94 V0](#)

[Contact material CuSn](#)

[Contact surface material Ni/Au](#)

[Contact carrier material PA 6.6](#)

[Material of grip body TPU, hardly inflammable, self-extinguishing](#)

[Material, knurls Zinc die-cast, nickel-plated](#)

[Sealing material NBR](#)

[Back to top](#)[Standards and Regulations](#)

[Flammability rating according to UL 94 V0](#)

[Back to top](#)[Cable](#)

[Cable type Ethernet](#)

[Cable type \(abbreviation\) 936](#)

[Cable structure 1x4xAWG22/7; SF/TQ](#)

[Conductor cross section 4x 0.34 mm²](#)

[AWG signal line 22](#)

[Conductor structure signal line 7x 0.25 mm](#)

[Core diameter including insulation 1.95 mm](#)

[Wire colors white-blue, orange-yellow](#)

[Overall twist Star quad](#)

[Shielding Plastic-coated aluminum foil, tinned copper braided shield](#)

[Optical shield covering 100 %](#)

[External sheath, color black RAL 9005](#)

[Outer sheath thickness >= 0....](#)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-MRDC2/ 5,0-936 SCO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.