

INDUSTRIAL COMPONENT DATA

SAC-4P-MRS/ 0,3-PUR/FRS PE SCO 1423226 PHOENIX CONTACT Power cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MRS/0,3-PUR/FRS PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MRS/0,3-PUR/FRS PE
Catalog number	1423226
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-B74BB6CB55
Generated	2026-08-03

Product Overview

Power cable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Power cable, 4-position, PUR halogen-free, black-gray RAL 7021, cable length: 0.3 m, for AC current up to 12 A/630 V

Key Commercial Data

Orderkey 1423226

Packing unit 1

GTIN 4055626338361

Custom tariff number 85444290

Dimensions

Length of cable 0.3 m

Ambient conditions

Degree of protection IP65

IP67

General

Rated current at 40°C 12 A

Rated voltage 690 V AC

Number of positions 4

Coding S power
Status display No
Protective circuit/component unwired
Overvoltage category III
Degree of pollution 3
Torque 0.4 Nm
Material
Flammability rating according to UL 94 V0
Contact material CuZn
Contact surface material Au
Contact carrier material PA
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Standards and Regulations
Flammability rating according to UL 94 V0
Cable
Cable type PUR halogen-free black
Cable type (abbreviation) PUR
Cable abbreviation Li9YV1-11Y
UL AWM style 20234 / 10492 (80°C/1000 V)
Conductor cross section 4x 1.5 mm²
AWG power supply 16
Conductor structure, voltage supply 78x 0.15 mm
Core diameter including insulation 2.45 mm ±0.05 mm
Thickness, insulation ≥ 0.36 mm
Wire colors Black 1, black 2, black 3, green/yellow
Overall twist 4 wires, twisted
Length of twist, overall twist 93 mm
External sheath, color black-gray RAL 7021
Outer sheath thickness approx. 1.3 mm
External cable diameter D 8.8 mm ±0.25 mm
Minimum bending radius, fixed installation 5 x D
Minimum bending radius, flexible installation 10 x D
Numbe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MRS/0,3-PUR/FRS PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.