


INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 1,5-542/M8 FR BK 1406217 PHOENIX CONTACT Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 1,5-542/M8 FR BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 1,5-542/M8 FR BK
Catalog number	1406217
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-19F90354F5
Generated	2026-08-06

Product Overview

Sensor/actuator cable

Sensor/actuator cable, 4-pole, PVC, yellow, M12 SPEEDCON straight male connector, coding: A, to M8 angled connection female, cable length: 1.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Key Commercial Data

Orderkey 1406217

Packing unit 1 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

GTIN 4046356798334

Weight per Piece (excluding packing) 22.220 g

Custom tariff number 85444290

Country of origin US (United States)

Dimensions

Length of cable 1.5 m

Ambient conditions

Ambient temperature (operation) -25 °C ... 90 °C (Plug / socket)

Degree of protection IP65
IP67
IP68
General
Rated current at 40°C 4 A
Rated voltage 48 V AC
60 V DC
Number of positions 4
Insulation resistance $\geq 100 \text{ M}\Omega$
Coding A - standard
Standards/regulations M12 connector IEC 61076-2-101
M8 connector IEC 61076-2-104
Status display No
Protective circuit/component unwired
Overvoltage category II
Degree of pollution 3
Insertion/withdrawal cycles ≥ 100
Torque 0.4 Nm (M12 connector)
0.2 Nm (M8 connectors)
Material
Flammability rating according to UL 94 HB
Contact material CuSn
Contact surface material Ni/Au
Contact carrier material TPU GF
Material of grip body TPU, hardly inflammable, self-extinguishing
Material, knurls Zinc die-cast, nickel-plated
Sealing material NBR
Standards and Regulations
Standard designation M12 connector
Standards/regulations IEC 61076-2-101
Standard designation M8 connector
Standards/regulations IEC 61076-2-104
Flammability rating according to UL 94 HB
Cable
Cable type PVC yellow 105 °C
Cable type (abbreviation) 542
UL AWM style 2517 (105 °C / 300 V)
AWG signal line 24
Conductor structure signal line 32x 1.10 mm
Core diameter including insulation 1.12 mm....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 1,5-542/M8 FR BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.