

INDUSTRIAL COMPONENT DATA

SAC-4P-M12MS/ 5,0-542 BK 1406225 PHOENIX CONTACT

Sensor/actuator cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-M12MS/ 5,0-542 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-M12MS/ 5,0-542 BK
Catalog number	1406225
Category	Sensor-actuator patch cord
Minimum order	50 Pcs
Document ID	EO-3C42178589
Generated	2026-08-06

Product Overview

Sensor/actuator cable

Sensor/Actuator Cable, 4-Pole, PVC, Yellow, M12 Straight Male Connector, Encoding: A, to Free Cable End, Cable Length: 5 m

Sensor/actuator cable, 4-position, PVC, yellow, Plug straight M12, coding: A, on free cable end, cable length: 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataProduct propertiesProduct type Sensor/actuator cable

Application Standard, U.S. cables

Number of positions 4

No. of cable outlets 1

Shielded no

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 HB

Material of grip body TPU, hardly inflammable, self-extinguishing

Contact material CuSn

Contact surface material Ni/Au
Contact carrier material TPU GF
Material for screw connection Zinc die-cast, nickel-plated
Outer sheath, material PVC
Electrical propertiesInsulation resistance $\geq 100 \text{ M}\Omega$
Nominal voltage UN 250 V AC
250 V DC
Nominal current IN 4 A
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
SignalingStatus display no
Status display present No
Connection dataConductor connection
Tightening torque 0.4 Nm (M12 connector)
ConnectorConnection 1
Type Plug straight M12
Coding type A
Connection 2
Type free cable end
Cable/lineCable length 5 m
PVC yellow 105 °C [542]
Dimensional drawing
Cable weight 36 kg/km
UL AWM Style 2517 (105 °C / 300 V)
Number of positions 4
Shielded no
Cable type PVC yellow 105 °C [542]
Conductor structure signal line 30x 1.30 mm
AWG signal line 22
Wire diameter incl. insulation 1.27 mm $\pm 0.03 \text{ mm}$
External cable diameter 5.00 mm $\pm 0.2 \text{ mm}$
Outer sheath, material PVC
External sheath, color yellow
Conductor material Tin-plated Cu litz wires
Material wire insulation PVC
Single wire, color brown, blue, black, white
Overall twist 4 wires, twist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-M12MS/ 5,0-542 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.