

INDUSTRIAL COMPONENT DATA

SAC-4P-P12MR/ 0,6-PUR/P12FS 1393590 PHOENIX CONTACT

Sensor/actuator cable, 4-pole, halogen-free PUR, grayish..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-P12MR/ 0,6-PUR/P12FS



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-P12MR/ 0,6-PUR/P12FS
Catalog number	1393590
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-5A70F017DB
Generated	2026-08-04

Product Overview

Sensor/actuator cable, 4-pole, halogen-free PUR, grayish black RAL 7021, M12 Push-pull angled connector, coding: A, a Straight female M12 Push-pull, coding: A, cable length: 0.6 m

Cable for sensors/actuators

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

ETIM for 1393590 Sensors (EC001855)

Feature Name

Feature Value

Number of poles (EF001391)

4

Type of electrical connection, field-sided (EF005525)

M12

Type of plug-in contact, field sided (EF006269)

Male (plug)

Positioning cable feed, field-sided (EF005928)

Angled

Type of electrical connection, box-sided (EF005524)

M12

Type of plug-in contact, box-sided (EF008386)
Female (bus)
Positioning cable feed, box-sided (EF005927)
Straight
Cable length (EF000536)
0.6 m
Material of cable sheath (EF004136)
Other
Halogen free (EF000025)
Yes
Colour cable sheath (EF008249)
Other
With LED indication (EF005950)
No
Screened (EF000881)
No
Cable type (EF000081)
Multi-core
Vulcanize (EF004115)
No
Material contact body (EF008248)
CuSn
Material of contact surface (EF004020)
Other
Permitted cable outer temperature after assembling without vibration (EF001686)
-40 °C
Permitted cable outer temperature during assembling/handling (EF001685)
-25 °C
Rated current I_n (EF008250)
4 A
Rated voltage (EF000228)
250 V
Degree of protection (IP) (EF005474)
IP65

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-P12MR/ 0,6-PUR/P12FS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.