

INDUSTRIAL COMPONENT DATA

SAC-4P-P12MR/ 1,5-PUR SH 1476850 PHOENIX CONTACT

Sensor/actuator cable, 4-pole, halogen-free PUR, greyish bl..

Brand: PHOENIX CONTACT | Manufacturer Part Number: SAC-4P-P12MR/ 1,5-PUR SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	SAC-4P-P12MR/ 1,5-PUR SH
Catalog number	1476850
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-23BA2359B5
Generated	2026-08-05

Product Overview

Sensor/actuator cable, 4-pole, halogen-free PUR, greyish black RAL 7021, shielded (Advanced Shielding Technology), M12 Push-pull angled connector, coding: A, to free cable end, cable length: 1.5 m

Sensor/actuator cable, 4-position, PUR halogen-free, black-gray RAL 7021, shielded (Advanced Shielding Technology), Plug angled M12 Push Pull, coding: A, on free cable end, cable length: 1.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial Field Connectivity (IFC)

Additional Product Information

Technical dataMountingConnection method Push-Pull

Product propertiesProduct type Sensor/actuator cable

Number of positions 4

Application Standard

No. of cable outlets 1

Shielded yes

Coding A

Insulation characteristics

Overvoltage category II

Degree of pollution 3

Material specificationsFlammability rating according to UL 94 V0

Outer sheath, material PUR

Conductor material Bare Cu litz wires
Electrical propertiesContact resistance $\leq 5\text{ m}\Omega$
Insulation resistance $\geq 100\text{ M}\Omega$
Nominal voltage UN 48 V AC
60 V DC
Nominal current IN 4 A
Protective circuit unwired
Max. conductor resistance $58\text{ m}\Omega/\text{km}$
Mechanical propertiesMechanical data
Insertion/withdrawal cycles ≥ 100
Max. bending cycles 10000000
SignalingStatus display No
Status display present No
Connection dataConnection technology
Connection method Push-Pull
Conductor connection
Connection method Push-Pull
ConnectorConnection 1
Type Plug angled M12 Push Pull
Locking type Push Pull
Coding type A
Connection 2
Type free cable end
Cable/lineCable length 1.5 m
PUR halogen-free black [PUR]
Dimensional drawing
Cable weight 36 kg/km
UL AWM Style 20549 / 10493 (80°C/300 V)
Number of positions 4
Shielded yes
Cable type PUR halogen-free black [PUR]
Conductor structure signal line 42x 0.10 mm
AWG signal line 22
Conductor cross section 4x 0.34 mm² (Signal line)
Wire diameter incl. insulation 1.27 mm $\pm 0.02\text{ mm}$ (Signal line)
External cable diameter 4.95 mm $\pm 0.2\text{ mm}$
Outer sheath, material PUR
External sheath, color black-gray RAL 7021
Conductor material...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / SAC-4P-P12MR/ 1,5-PUR SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.